

UPS Remote Monitor



The SD3 is a sophisticated warning system utilising GSM technology which puts configuration, control and response at the fingertips of users. Any UPS trigger is communicated by text and/or voice messages to pre-determined landline or mobile phone numbers, enabling owners to respond appropriately, even resetting devices or talking to the premises remotely. The end user can choose up to 10 contact telephone numbers and types of message (voice or SMS text), created to suit their requirements. Has an integral thermometer which can be pre-set at any given temperature from 0°C to 40°C and the SD3 will transmit a message when the temperature has been exceeded or reached. Supplied with a remote aerial as standard for best reception.



The SD3 may be connected to a standard phone line and configured to dial GSM or Landline or both for additional security

The unit is powered from a standard non UPS mains socket via a wall mounted battery box with an 7Ahr battery backup providing power in the event of a power outage



A programmable remote access feature lets you dial into the unit via fixed land line or mobile phone from anywhere in the world, and access four programmable outputs that can remotely switch electrical apparatus or switch on indicators.

Supplied without SIM Card – standard SIM requires to be unlocked & registered on network

Mpower will supply SD3 Remote Monitor battery box + 7Ahr VRLA battery and commission if require to an existing compatible UPS system or as part of a new system installation or upgrade

Please contact sales or service for more information on price & availability

sales@mpowerups.co.uk



service@mpowerups.co.uk



Mpower Web Site
www.mpowerups.co.uk



Our UPS Commerce Site
www.boxups.co.uk



Mpower Phone 01420 82031

Mpower Fax 01420 82068

Technical Specification

	Description
Supply voltage	10.5 - 28vDC
Current consumption (at 12vDC)	50mA (standby) 170mA (active)
Trigger inputs	8: positive/negative applied or positive/negative removed (5 - 24vDC)
Outputs	4 x open-collector (OC) switched -ve at 100mA
Telecommunications approval	CTR21
REN rating for PSTN connection	1
Dialling format	DTMF
Dimensions (H X W X D)	140mm x115mm x 30mm
Operating environment	-10°C to 55°C
Sim card	Accepts any standard GSM/GPRS mobile telephone network SIM card